



# DIVERSE URETHANES

---

---

## PRODUCT DATA SHEET

---

---

### PBS H 1000 Polyol with PBS H 1000 ISO

#### 1. INTRODUCTION

PBS H 1000 POLYOL is a polyether based polyol blend which, when reacted with PBS H 1000 ISO using suitable two-component air assisted low pressure spray equipment or high pressure spray equipment, yields a high quality, high performance, solvent-free 85 to 90 Shore A elastomeric coatings.

The reaction between the two components takes place rapidly, allowing material to be applied to vertical surfaces without sag. At the same time, good initial flow is retained, resulting in coatings having an even, consistent thickness with good surface finish.

#### 2. APPLICATIONS

PBS H 1000 POLYOL is ideal for the lining of surfaces which are subjected to high wear and tear as well as areas where high performance products are required.

#### 3. CONSIDERATIONS

As with all polyurethane products, the product should not be exposed to very strong acids or bases. The highest temperature at which the product should be used is 80-85°C in order to maintain the full physical properties. The material can tolerate short period temperature increases up to approximately 120°C without permanently impairing any of the physical properties.

#### 4. PBS H 1000 POLYOL PHYSICAL PROPERTIES

Appearance	:	Black liquid
Viscosity at 25° (cP)	:	600 - 1700
Specific gravity at 25°	:	1.00 (±0.02)

## 5. **PBS H 1000 ISO PHYSICAL PROPERTIES**

Appearance	:	White liquid
Viscosity at 25° (cP)	:	200 – 600cps
Specific gravity at 25°C	:	1.14 (±0.02)

## 6. **ELASTOMERS**

The following range of physical properties are typical of the results obtained from the laboratory evaluation of PBS H 1000 POLYOL, reacted with PBS H 1000 ISO at 0.92% stoichiometry and subjected to the correct post curing cycle.

PBS H 1000 POLYOL at ~25°C 100 parts by weight or 100 parts by volume  
PBS H 1000 ISO at ~25°C 114 parts by weight or 100 parts by volume

Pot life (seconds) @ 25°C	:	17 - 23	
Hardness (Shore A Sprayed)	:	85 - 90	
Density (gcm <sup>-3</sup> )	:	1,02 - 1,07	
Tensile Strength (MPa)	:	9 - 15	DIN 53504
Elongation at break (%)	:	80 - 120	DIN 53504
Tear Resistance (Nmm <sup>-1</sup> )	:	17 - 25	DIN 53515

## 7. **PROCESSING**

The PBS H 1000 POLYOL component is a blend which may separate during storage. Drums should therefore be agitated before use to ensure homogeneity.

The system should only be processed using suitable two-component, air assisted spray equipment. Information on recommended types will be provided on request.

The aerosol produced whilst spraying can be hazardous to health, and operators should be protected with air-fed full face masks or, alternatively, a high volume, powerful extraction system. The system must be processed in a dry environment as exposure to moisture, or spraying in high humidity could result in foaming.

The surface to be coated must be properly prepared by roughening the metal with a wire brush or grinding disk, and the loose material brushed away or blown off with compressed air. Do not try to clean the surface with a solvent that contains any contaminants (e.g. grease, thinners etc) as this may result in blisters forming under the sprayed surface. If a solvent is used, ensure it has completely evaporated off the surface before commencing spraying.

The compressed air should be properly dried before entering the machine or the machine's day tanks, which should also be sealed so as to prevent the ingress of any moisture which could react with the PBS H 1000 ISO and cause it to solidify.

## **8. PACKAGING**

Standard packs consist steel drums containing 25kg PBS H 1000 POLYOL, 25kg PBS H 1000 ISO. Alternative packaging may be supplied on request.

## **9. STORAGE**

### **9.1 PBS H 1000 POLYOL**

Should be stored under cover in a dry environment. Partly used containers should be resealed immediately after use to minimise any contamination from atmospheric moisture.

### **9.2 PBS H 1000 ISO**

Should be stored between 20 - 30°C, as crystallisation will occur after prolonged storage at temperatures below 15°C.

In the event of such crystallisation, PBS H 1000 ISO should be heated to 70 - 80°C, thoroughly agitated to ensure homogeneity, the cooled to 20°C before use. Should this material remain crystalline however, irreversible degradation has taken place, rendering the material unfit for use.

## **10. HANDLING**

### **10.1 PBS H 1000 POLYOL**

PBS H 1000 POLYOL does not represent a significant health risk to users under normal conditions of industrial exposure. Though it is mercury free, it still does contain an organic, heavy metal catalyst which is toxic by ingestion.

### **10.2 PBS H 1000 ISO**

PBS H 1000 ISO is an isocyanate containing material and normal standards of industrial hygiene should be observed during its handling. Safety goggles, gloves and overalls should be worn and the material should be used in a well ventilated area. Inhalation of vapours and aerosol should be avoided.

## **11. FIRST AID MEASURES**

### **11.1 PBS H 1000 POLYOL**

In case of skin contact with PBS H 100 POLYOL, the affected area must be washed with soap and water. Eye contamination should be treated by rinsing with running water for at least 10 minutes. Seek medical assistance.

## 11.2 **PBS H 1000 ISO**

PBS H 1000 ISO may be dermatitic and exhibits a low order of toxicity, however since it is possible that certain individuals may be unusually sensitive to this material, it is recommended that all users wash thoroughly and avoid prolonged and repeated contact. Eye contamination, will cause severe irritation and pain. Immediate rinsing with water must be initiated and continued for at least 10 minutes. (See attached Safety data Sheet). Seek medical assistance.

## 12. **FIRE**

Keep drums cool by spraying them with water if they are exposed to fire. Extinguish with dry chemical, foam, sand or water spray.

## 13. **SPILLAGES AND WASTE DISPOSAL**

### 13.1 **PBS H 1000 POLYOL**

Drum as much as possible of the spill, and wash away the remains with copious amounts of water.

### 13.2 **PBS H 1000 ISO**

Decontamination can be affected by overnight contact with liberal amounts of a solution containing methanol (30 parts), water (70 parts), concentrated ammonia (1 part) and detergent (1 part). Drums should not be resealed until decontamination is complete. (See attached Safety Data Sheet on details for Dealing with Larger Spills).

### 13.3 **Waste Disposal**

Customers are advised to check their local, provincial or national legislation governing the disposal of waste material.

PBS H 1000 ISO is an isocyanate containing material and is considered hazardous by inhalation.

The information provided in this data sheet and otherwise supplied to users is based on our general experience and upon tests which are believed to be reliable. However, because we have no control over the exact manner in which the information is used, we cannot guarantee the results to be obtained. Furthermore we make no express or implied warranty of merchantability or fitness of the product for a particular use.

The information contained in this data sheet is correct and accurate to the best of our knowledge but without warranty or liability.

All tests are carried out according to the standard methods used by Urochem and details may be supplied on request.

All sales of this product shall be subject to Urochem's Standard Conditions of Sale.

## **SAFETY DATA SHEET**

### **PBS H 1000 ISO**

1. **IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND COMPANY / UNDERTAKING:**

Product Name : PBS H 1000 ISO

Address : Urochem  
No:1 High Street  
Modderfontein  
EDENVALE 1610

Emergency Telephone No : (011) 606-2413

2. **COMPOSITION/INFORMATION ON INGREDIENTS**

**Product Description**

Diisocyanato diphenylmethane (MDI) based composition.

<b><u>Hazardous</u></b>	<b><u>Cas No.</u></b>	<b><u>% (w/w)</u></b>	<b><u>Symbol</u></b>	<b><u>R Phrases</u></b>
Diphenylmethanediisocyanate, isomers and homologues	009016-87-9	>25	Xn	R20 R42 R36/37/38

3. **HAZARDS IDENTIFICATION**

Harmful by inhalation.

This product is a respiratory irritant and potential respiratory sensitiser: Repeated inhalation of vapour or aerosol at levels above the occupational exposure limit could cause respiratory sensitisation. The onset of the respiratory symptoms may be delayed for several hours after exposure. A hyper-reactive response to even minimal concentrations of MDI may develop in sensitised persons. Irritating to eyes and skin.

Repeated and/or prolonged contact may cause skin sensitisation.

Irritating to eyes and skin.

Reacts slowly with water to produce carbon dioxide which may rupture closed containers. This reaction accelerates at higher temperatures.

#### 4. **FIRST AID MEASURES**

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

##### **Inhalation**

Remove patient from exposure, keep warm and at rest. Obtain medical attention. Treatment is symptomatic for primary irritation or bronchospasm. If breathing is laboured, oxygen should be administered by qualified personnel. Apply artificial respiration if breathing has ceased or shows signs of failing.

##### **Skin Contact**

Remove contaminated clothing. Wash immediately with water followed by soap and water. If symptoms develop, obtain medical attention. Contaminated clothing should be thoroughly cleaned.

##### **Eye Contact**

Immediately irrigate with eyewash solution or clean water, holding the eyelids apart, for at least 10 minutes. Obtain immediate medical attention.

##### **Ingestion**

Provided the patient is conscious, wash out mouth with water and give 200-300 ml (half a pint) of water to drink. Do not induce vomiting. Obtain immediate medical attention.

##### **Further Medical Treatment**

Symptomatic treatment and supportive therapy as indicated. Following severe exposure the patient should be kept under medical review for at least 48 hours.

#### 5. **FIRE-FIGHTING MEASURES**

Not classed as flammable.

If involved in a fire, it may emit noxious and toxic fumes.

Containers may burst if overheated.

Due to reaction with water producing CO<sub>2</sub>-gas, a hazardous build-up of pressure could result if contaminated containers are re-sealed.

Combustion products may include: carbon monoxide, carbon dioxide, nitrogen oxides, hydrocarbons and HCN.

### **Extinguishing Media**

Foam, CO<sub>2</sub> or dry powder. Water may be used if no other available and then in copious quantities. Reaction between water and hot isocyanate may be vigorous. Prevent washings from entering water courses, keep fire exposed containers cool by spraying with water

### **Fire Fighting Protective Equipment**

Suitable respiratory protection with full face piece and positive air supply. PVC boots, gloves, and protective clothing should be worn.

## 6. **ACCIDENTAL RELEASE MEASURES**

Clean-up should only be performed by trained personnel. People dealing with major spillage's should wear full protective clothing including respiratory protection.

Evacuate the area. Prevent further leakage, spillage or entry into drains.

Absorb spillage's onto sand, earth or any suitable absorbent material. Do not absorb onto sawdust or other combustible materials. Shovel into open-top drums for further decontamination. Wash the spillage's area clean with liquid decontaminant. Test atmosphere for MDI vapour.

Neutralise small spillage's with decontaminant. Remove and dispose of residues.

The compositions of liquid decontaminants are given in Section 16.

See also brochure PU 193-1 (see section 16).

## 7. **HANDLING AND STORAGE**

### 7.1 **Handling**

Do not breathe vapour/spray. Avoid contact with skin and eyes. Atmospheric concentrations should be minimised and kept as low and reasonably practicable below the occupation exposure limit. The efficiency of the ventilation must be monitored regularly because of the possibility of blockage.

When the product is sprayed or heated, suitable respiratory protection equipment with positive air supply may be required. Keep equipment clean. A basic essential in sampling, handling and storage is the prevention of contact with water.

Keep stocks of decontaminant readily available. The compositions of liquid decontaminants are given in section 16. See also brochure PU 193-1 (see section 16).

## 7.2 **Storage**

Keep containers properly sealed and store indoors in a well ventilated area. Keep away from frost. Keep away from moisture. If a container is contaminated, do not reseal it. Due to reaction with water producing CO<sub>2</sub>-gas, a hazardous build-up of pressure could result if contaminated containers are re-sealed.

Unsuitable containers : copper, copper alloy and galvanised surfaces.

Suitable containers : stainless steel or mild steel.

Storage Temperature : 15 - 35°C.

## 8. **EXPOSURE CONTROLS/PERSONAL PROTECTION**

Wear suitable protective clothing, gloves and eye/face protection. MDI can only be smelled if the occupational exposure limit has been exceeded considerably. Atmospheric concentrations should be minimised and kept as low as reasonably practicable below the occupational exposure limit.

Medical supervision of all employees who handle or come in contact with respiratory sensitisers is recommended. Personnel with a history of asthma-type conditions, bronchitis or skin sensitisation conditions should not work with MDI based products.

The Occupational Exposure Limits listed below do not apply to previously sensitised individuals. Sensitised individuals should be removed from any further exposure.

### **Respirators**

Suitable respiratory equipment with positive air supply should be used in cases of insufficient ventilation or where operational procedures demand it.

### **Eye Protection**

Chemical safety goggles. Full face shield if splashing is possible.

### **Gloves**

The following protective materials are recommended:

- Neoprene.
- Nitrile butadiene rubber.
- Butyl rubber.
- PVC (Heavy duty).

Thin disposable gloves should be avoided for repeated or long term use.



## Other

Overalls (preferably heavy cotton) or Tyvek-Pro Tech "C", Tyvek-Pro "F" disposable overall. Contaminated clothing should be thoroughly cleaned before re-use.

## Occupational Exposure Limits

Hazardous Ingredient(s)	LTEL ppm	8hr TWA mg/m <sup>3</sup>	STEL ppm mg/m <sup>3</sup>	Notes
Isocyanates, all (as -NCO) (Diphenylmethane 4,4'diisocyanate)	-	0.02	- 0.07	MEL Sen

## 9. STABILITY AND REACTIVITY

Incompatible materials and conditions: water, alcohol's, amines, bases and acids. Avoid high temperatures.

### Hazardous Reactions

Stable at room temperature. Reaction with water (moisture) produces CO<sub>2</sub>-gas. Exothermic reaction with materials containing active hydrogen groups. The reaction becomes progressively more vigorous and can be violent at higher temperatures if the miscibility of the reaction partners is good or is supported by stirring or by the presence of solvents.

### Hazardous Decomposition Product(s)

Highly unlikely under normal industrial use

## 10. TOXICOLOGICAL INFORMATION

This health hazard assessment is based on information available on similar products.

### Inhalation

This product is a respiratory irritant and potential respiratory sensitiser; repeated inhalation of vapour or aerosol at levels above the occupational exposure limit could cause respiratory sensitisation. Symptoms may include irritation to the eyes, nose, throat and lungs, possibility combined with dryness of the throat, tightness of chest and difficulty in breathing. The onset of the respiratory symptoms may be delayed for several hours after exposure. A hyper-reactive response to even minimal concentrations of MDI may develop in sensitised persons.

Median Lethal Concentration (4 hrs) (respirable aerosol) : 490 mg/m<sup>3</sup> (rat).

### **Skin Contact**

Moderate irritant.

Repeated and/or prolonged contact may cause skin sensitisation.

Animal studies have shown that respiratory sensitisation can be induced by skin contact with known respiratory sensitiser including diisocyanates. These results emphasise the need for protective clothing including gloves to be worn at all times when handling these chemicals or in maintenance work.

Dermal Median Lethal Dose : > 5000 mg/kg (rabbit).

### **Eye Contact**

The vapour, aerosol and liquid are irritant.

### **Ingestion**

Low oral toxicity. Ingestion may cause irritation of the gastrointestinal tract.

Oral Median Lethal Dose > 5000 mg/kg (rat).

### **Long Term Exposure**

Rats have been exposed for two years to a respirable aerosol of polymeric MDI which resulted in chronic pulmonary irritation at high concentrations. Only at the top level (6 mg/m<sup>3</sup>), there was a significant incidence of a benign tumour of the lung (adenoma) and one malignant tumour (adenocarcinoma). There were no lung tumours at 1 mg/m<sup>3</sup> and no effects at 0.2 mg/m<sup>3</sup>. Overall, the tumour incidence, both benign and malignant, and the number of animals with the tumours were not different from controls. The increased incidence of lung tumours is associated with prolonged respiratory irritation and the concurrent accumulation of yellow material in the lung, which occurred throughout the study. In the absence of prolonged exposure to high concentrations leading to chronic irritation and lung damage, it is highly unlikely that tumour formation will occur. Industrial experience in humans has not shown any links between MDI exposure and cancer developments.

There are reports that chronic exposure by inhalation may result in permanent decrease in lung function.

No birth defects were seen in two independent animal (rat) studies. Fetotoxicity was observed at doses that were extremely toxic (including lethal) to the mother. fetotoxicity was not observed at doses that were not maternally toxic. The doses used in these studies were maximal, respirable concentrations, which are well in excess of defined occupational exposure limits.

There is no substantial evidence of mutagenic potential.

## 11. **ECOLOGICAL INFORMATION**

### **Environmental Fate and Distribution**

By considering the production and use of the substance, it is unlikely that significant environmental exposure in the air or water will arise.

### **Persistence and Degradation**

Immiscible with water, but will react with water to produce inert and non-biodegradable solids. Conversion to soluble products, including diamino - diphenylmethane (MDA), is very low under the optimal laboratory conditions of good dispersion and low concentration. In air, the predominant degradation process is predicted to be a relatively rapid OH radical attack, by calculation and by analogy with related diisocyanates.

### **Toxicity**

By comparison with an analogous product, the following values are anticipated.

LCO (zebra fish) > 1000 mg/1  
EC50 (Daphnia magna) (24 hour) > 1000 mg/1  
EC50 (E.Coli) > 100 mg/1

The measured ecotoxicity is that of the hydrolysed product, generally under conditions maximising production of soluble species. Even so, the observed ecotoxicity is low/very low. A pond study showed gross contamination caused no significant toxic effects on a wide variety of flora in all trophic levels (including fish). no detectable diaminodiphenylmethane (MDA), and no evidence of bioaccumulation of MDI or MDA.

## 12. **DISPOSAL CONSIDERATIONS**

The generation of waste should be avoided or minimised wherever possible. Disposal should be in accordance with local, state or national legislation. Untreated material is not suitable for disposal. Waste, even small quantities, should never be poured down drains, sewers or water courses.

Small quantities and empty drums - pretreat to neutralise prior to disposal.

Large quantities - incinerate under approved controlled conditions, using incinerators suitable for the disposal of noxious chemical waste. Empty drums should be decontaminated and either passed to an approved drum reconditioner or destroyed.

See also brochure PU 193-1 (see section 16).

## 13. **TRANSPORT INFORMATION**

Not classified as dangerous for transport.

#### 14. **REGULATORY INFORMATION**

EC Classification	:	HARMFUL
Hazard Symbol	:	Xn
Risk Phrases	:	R20 - Harmful by inhalation. R36/37/38 - Irritating to eyes, respiratory system and skin.
	:	R42 - May cause sensitisation by inhalation.
Safety Phrases	:	S22 - Do not breathe dust. S26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S28 - After contact with skin, wash immediately with plenty of warm soapy water. S38 - In case of insufficient ventilation, wear suitable respiratory equipment. S45 - In case of accident or if you feel unwell seek medical advice immediately (show the label where possible).

#### 15. **OTHER INFORMATION**

This data sheet was prepared in accordance with Directive 93/112/EC.

Liquid MDI decontaminants:

Decontaminant 1 :

-	Water	-	90%
-	Concentrated ammonia solution	-	8%
-	Liquid detergent	-	2%

Decontaminant 2 :

-	Water 90	-	95%
-	Sodium carbonate	-	5 - 10%
-	Liquid detergent	-	0.2 - 0.5%

Decontaminant 1 contains ammonia. Ammonia presents health hazards. (See supplier safety information).

Decontaminant 2 reacts slower with MDI but is more environmentally friendly than decontaminant 1.

<b>Chemical Resistance ASTM D 3912</b>			
Methanol	<b>D</b>	Sulfuric acid / 5 %	<b>A</b>
Gasoline	<b>C</b>	Sulfuric acid / 10%	<b>A</b>
Diesel Fuel	<b>A</b>	Hydrochloric acid / 5%	<b>A</b>
Toluene	<b>E</b>	Hydrochloric acid / 10%	<b>A</b>
MTBE	<b>B</b>	Phosphoric acid / 10%	<b>A</b>
5% MTBE ? Gasoline	<b>B</b>	Ammonium hydroxide / 10%	<b>A</b>
Motor oil	<b>C</b>	Ammonium hydroxide / 20%	<b>A</b>
Hydraulic fluid	<b>A</b>	Sodium hydroxide / 10%	<b>A</b>
2-Methylbutane	<b>A</b>	Sodium hydroxide / 20%	<b>A</b>
Water room temperature	<b>A</b>	Sodium hydroxide / 50%	<b>C</b>
Water 82°C 14 days	<b>A</b>	Sodium hydroxide 1% 50°C 14 days	<b>C</b>
10% NaCL water room temp	<b>A</b>	Potassium hydroxide 10%	<b>A</b>
10% NaCL water 50°C 14 days	<b>A</b>	Potassium hydroxide 20%	<b>C</b>
10% Sugar Water	<b>A</b>	Acetic acid	<b>A</b>

- A - no visible damage
- B - Slight surface change
- C - Slight surface discolour, no hardness loss
- D - Swelling 48 hrs
- E - Swelling 24 hrs